

Sentinel X500

Inhibited Antifreeze for Central Heating Systems

Features & Benefits

- Controls scale and corrosion
- Effective frost protection
- Helps prevent the formation of hydrogen gas
- Helps prevent boiler noise
- Suitable for all metals including aluminium
- Non-toxic and biodegradable
- Concentration is easily checked with a Sentinel Test Kit or a conductivity meter
- Manufactured under a quality system conforming to ISO9001

Application

Sentinel X500 is a multipurpose inhibited antifreeze formulated to help control corrosion, scale, boiler noise and hydrogen gassing in all types of indirect heating systems including those containing aluminium components. If minimum levels are maintained the product ensures a permanent protection and does not need to be replaced. Sentinel X500 is suitable for use in all waters, both hard and soft. The low toxicity formulation is colourless and easy to handle.

Dosing & Feeding

The dosage of Sentinel X500 will depend on the level of frost protection required. One 20L pail of Sentinel X500 added to a typical domestic system of 8 to 10 radiator panels will provide the minimum concentration of corrosion and scale inhibitor and also protection from freezing down to approximately -6°C. Two 20L pails will provide protection to -20°C. A dosage of 20% or more is needed to achieve the minimum concentration of corrosion and scale inhibitor.

The Sentinel Test Kit can be used to verify that this level has been reached. To determine the precise glycol concentration, a refractometer is required. Further information is available upon request.

For best results, it is recommended that systems are cleansed and flushed in accordance with BS7593; new systems and those up to 6 months old with Sentinel X300, existing systems with Sentinel X400. If the system is already noisy due to limescale deposits in the heat exchanger, Sentinel X200 should be added together with Sentinel X500.

Open Systems: Dose via F&E cistern, via a by-pass feeder or use a Sentinel Dosing Vessel.

Sealed Systems: If the system is empty, add to any convenient point before filling. If full, use a Sentinel Dosing Vessel to inject via the filling loop or other access point.

Physical Properties

- Appearance: Clear colourless liquid
- Odour: Mild slightly sweet
- Specific gravity: 1.04 (20°C)
- pH in aqueous solution (5%): 6.5 (approx)
- Freezing point: -58°C

Packaging

- 5 litre cubitainer
- 10 litre cubitainer
- 1000 litre semi-bulk container

Safety Precautions

The information provided overleaf enables compliance with the Control of Substances Hazardous to Health Regulations. A full Safety Data Sheet is available upon request.

Sentinel X500

Inhibited Antifreeze for Central Heating Systems	A solution of inorganic and organic corrosion and scale inhibitors in propylene glycol.
Health Hazards	Not for use in potable water systems. Not considered hazardous to health.
Handling	Avoid contact with skin and eyes. Keep out of reach of children and animals. Wash out empty container thoroughly with water before disposal.
Storage	Keep container tightly closed. Store in cool, well ventilated area.
Spillage	Flush spillage with plenty of water and wash to waste. On soil: Absorb on to inert material and dispose of according to Controlled Waste Regulations.
Fire/Explosion Risks	Non-flammable. Oxides of carbon and nitrogen evolved in fire.
First Aid	Skin Exposure : Wash immediately with plenty of water. Eye Exposure : Rinse immediately with plenty of water. Seek medical attention. Ingestion : Rinse mouth with water. Do NOT induce vomiting! Seek medical attention.